

CapnoTrue® AMP and CapnoTrue® ASP Mainstream and Sidestream CO₂/SpO₂ Monitors

Advanced and reliable capnograph and pulse oximeter combined in a single monitor.



Key features of CapnoTrue® AMP

- Mainstream CO₂ measurement with the **IRMA CO₂ Analyzer**
- Warm-up time: < 10 seconds full specification
- Direct measurement without time delay
- Small, light-weight and shock-resistant: the **IRMA CO₂ Analyzer** weighs less than 30 g
- Adult/paediatric and infant **IRMA Airway Adapters**
- Plug and measure technology
- **IRMA Airway Adapters** with non-condensing light transmission XTP™ window
- No occlusion by water or mucus possible
- Maintenance and calibration-free technology
- Full range of key technology accessories
- Wide range of high-quality SpO₂ sensors

Key features of CapnoTrue® ASP

- Sidestream CO₂ measurement with the **ISA CO₂ Analyzer** and Nomo technology
- Warm-up time: < 10 seconds full specification
- Specially designed for low flow applications: 50 ml/min sampling flow for all applications, from adults to infants
- For intubated and non-intubated patients
- Maintenance and calibration-free technology
- The **Nomo Adapter** is specifically designed to remove water and water vapour from the sampled gas
- The **Nomo Adapter** includes a hydrophobic bacterial filter to protect against water intrusion and cross contamination
- Full range of key technology accessories
- Wide range of high-quality SpO₂ sensors

Delivery package of CapnoTrue® AMP

- Mainstream device
- IRMA CO₂ Analyzer
- IRMA Airway Adapter (adult/paediatric)
- Reusable SpO₂ sensor
- USB data cable
- CapnoTrue® power supply (EU and UK plug)
- 4 batteries (AA)
- 1 Li-ion rechargeable battery
- Silicone protective cover
- PC software
- Instruction manual

Delivery package of CapnoTrue® ASP

- Sidestream device
- Nomo Adapter
- Sampling line
- Sidestream airway adapter (adult/paediatric)
- Reusable SpO₂ sensor
- USB data cable
- CapnoTrue® power supply (EU and UK plug)
- 4 batteries (AA)
- 1 Li-ion rechargeable battery
- Silicone protective cover
- PC software
- Instruction manual


For further accessories, please visit www.bluepoint-medical.com

Technical data

| Specification | | |
|--|---|--|
| Measurement Range | etCO ₂ and FiCO ₂ | 0 - 15 % |
| | SpO ₂ | 0 - 100 % |
| | Respiration Rate | 0 - 150 1/min |
| | Pulse Rate | 20 - 300 1/min |
| Accuracy | etCO ₂ and FiCO ₂ | +/- (0.2 Vol % + 2 % of reading) +/- (0.3 Vol % + 4 % of reading) incl. interfering gases |
| | SpO ₂ | +/- 2 % (70 - 100%) |
| | Respiration Rate | +/-1 digit |
| | Pulse Rate | +/-1 digit (up to 100 1/min) or +/- 1 % (> 100 1/min) |
| Display | | |
| Parameters displayed | Numerical | End-tidal (et) CO ₂ and inspired (Fi) CO ₂ in Vol %, kPa or mmHg, oxygen saturation (SpO ₂), Respiration Rate (RR), Pulse Rate (PR), capnogram, plethysmogram and short term trend |
| | Indicators | Signal strength and signal quality, pulse amplitude, battery status, alarm mute, pulse tone mute, storage status, real-time mode, neonatal mode, time |
| Characteristics | Active OLED colour graphic display, 262 000 colours, 240 x 320 pixel | |
| Trend information | | |
| Long term trend | up to 400 hours | |
| Short term trend | 15 min/1 h/6 h | |
| Language versions | | |
| Please indicate language version when ordering | Europe: | EN, DE, ES, FR, IT, NL, S, RU, FI (additional language versions on request) |
| | Asia: | EN, CN, JP (additional language versions on request) |
| Environmental conditions | | |
| Operation | 0 - 50 °C, 15 - 95 % RH (non-condensing), 60 - 120 kPa (excl. Li-ion battery) | |
| Storage | -30 - 70 °C, 10 - 95 % RH (non-condensing), 60 - 120 kPa (excl. Li-ion battery) | |
| Classification | | |
| Product class | IIb (in accordance with MDD 93 / 42 / EEC) | |
| Safety | Class of protection II / Type BF – Type and degree of protection against electrical shock | |
| Construction | IPX1 (with silicone protective cover) | |
| Standards | EN 60601-1-1:1988; IEC 60601-1-2:2007; IEC 60601-1-4:2000; IEC 60601-1-8:2006; ISO 21647:2004; ISO 9919:2005; ISO 5356-1:2004; DIN EN 1789:2007, EN864:1996 | |
| Miscellaneous | | |
| Dimensions (L x W x D) | 150 mm x 75 mm x 35 mm | |
| Weight | < 400 g (complete device with batteries) | |
| Power supply | Power supply 90 - 260 V AC / 6 V DC, 50 - 60 Hz, 4 AA batteries, 2.5 Ah Li-ion battery | |
| Battery capacity | up to 6 hours continuous operation | |
| Communication interface | USB 2.0 | |

Specification subject to change

bluepoint® MEDICAL sales partner



The **CapnoTrue® AMP** and **ASP CO₂/SpO₂ Monitors** including the **IRMA CO₂ Analyzer**, **ISA CO₂ Analyzer** and **SoftCap® Sensors** are classified and certified as class IIb products.

For further information, please visit www.bluepoint-medical.com

bluepoint MEDICAL

CapnoTrue® – CO₂/SpO₂ Monitor Ultra-compact and ergonomic



» PRODUCTS that care for you «



Made in Europe

German and Swedish Technology



SoftCap® and SoftCap® A

» 3rd generation of soft sensors

Ultimate performance in capnography and pulse oximetry

The ultra-compact, ergonomic design of CapnoTrue® combines outstanding performance and reliability in mainstream or sidestream CO₂ and SpO₂ monitoring.

- High performance capnography with either mainstream or sidestream measurement
- Advanced pulse oximetry combining innovative technologies with advanced features
- Application range from infants to adults
- Display of etCO₂, FiCO₂, SpO₂, Respiration and Pulse Rate, capnogram and plethysmogram
- For intubated and non-intubated patients
- Maintenance and calibration-free technology
- Small, light-weight and shock-resistant mainstream IRMA CO₂ Analyzer
- Low flow sidestream sampling with the new Nomo technology
- Superior performance, easy to use and ergonomic design
- Up to 6 hours battery operation for extended transport time
- Storage capacity for patient data of up to 400 h
- USB interface and PC software
- Up to 16 language versions available
- Key technology accessories ensure reliable monitoring
- Autoclavable **SoftCap® A** and other high-quality SpO₂ reusable and disposable sensors
- Two years warranty



Applications

- CapnoTrue® AMP and ASP are well suited for:
- Patient transport within and between hospitals
 - Rescue services and emergency medicine
 - Resuscitation
 - General and PICU
 - Ventilator management and weaning

Key Technology Accessories

The CapnoTrue® provides you with leading technology sensors and accessories.

SpO₂ sensors

A wide range of flexible, robust and hygienic adult and paediatric SpO₂ sensors is available, including the 3rd generation soft sensors, fingerclip, wrap and ear sensors, as well as disposable sensors for use on adults through to neonates.

With the new **SoftCap® A Sensors**, it is possible for the first time to **autoclave SpO₂ sensors at 134°C**, thus eliminating the risk of nosocomial infections, resulting from pathogenic microorganisms or multi-resistant germs. All reusable sensors are supplied with a **two-year-warranty**.

For further information, please visit www.bluepoint-medical.com

Available sensors



SoftCap® SC SoftCap® SCA SoftCap® SCP SoftCap® SCPA SoftFlap® SF SoftWrap® W Disposables Ear Sensor EP

CapnoTrue® AMP Accessories

Mainstream measurement

The 30 grams IRMA CO₂ Analyzer sets new standards in CO₂ monitoring and provides reliable and easy CO₂ monitoring by mainstream measurement without time delay.

- Small and light-weight
- Plug and measure technology
- Shock resistant
- Two years warranty

The IRMA Airway Adapters are supplied in two versions for adult/paediatric and infant applications.

- Non-condensing light transmission XTP™ window
- Low dead space



IRMA Airway Adapter and IRMA CO₂ Analyzer

CapnoTrue® ASP Accessories

Sidestream measurement

In combination with the Nomo technology that removes water from the sampled gas, the ISA CO₂ Analyzer delivers highest performance in an ultra-compact format.

The **Nomo Adapter** incorporates a unique water separation section made of a special polymer with an integrated hydrophobic bacterial filter. The **Nomo Adapter** passes water vapour and condensed water through its membrane-like surface and evaporates it into the surrounding air, while leaving the carbon dioxide concentration unaffected.

The Nomo technology allows for up to two weeks of continuous monitoring with high moisture containing breathing gases – a first for capnography.

The Nomo Adapter contains a hydrophobic bacterial filter (efficiency ≥ 99.9980 %) to protect the ISA CO₂ Analyzer from water intrusion and cross contamination.



Nomo Adapter



Sampling line



Infant Adapter



Adult Adapter

